



JV090001

Derby Range

**Nickel Plated Brass
2-Piece Ball Valve
c/w Operating Lever**

BSPB Threaded



A WRAS approved economical and versatile nickel plated, brass bodied full bore ball valve suitable for gas and water applications.

The quarter turn operation in conjunction with the PTFE seats provides fast positive isolation.

Full bore construction minimises headloss and the hard chrome plated ball offers excellent wear resistance.

Approvals, Features & Benefits

- WRAS approved product*
- BSI Gas approved to EN331*
- Lightweight & economic
- PTFE seats $\frac{3}{4}$ "
- Full bore
- Lever operated

* $\frac{1}{4}$ " to 2" only

Pressure & Temperature

Pressure range :-

- $\frac{1}{4}$ " - $\frac{1}{2}$ " PN40 rated
- $\frac{3}{4}$ " - 1" PN32 rated
- $1\frac{1}{4}$ " - $2\frac{1}{2}$ " PN25 rated
- 3" - 4" PN16 rated

Gas temperature range:-

-20°C to 70°C

Liquid temperature range:-

-20°C to 110°C

BSPP	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	4
A	45	45	57	65	79	89	98	120	126	147	177
B	48	48	55	66	70	83	93	102	143	153	187
Weight Kg	0.12	0.12	0.17	0.27	0.41	0.64	0.90	1.54	2.04	3.42	5.86

MATERIALS	
Body	Nickel Plated Brass
Ball	Chrome Plated Brass
Stem	Brass
Stem O-rings	NBR
Seats	PTFE
Lever	Yellow PCV Coated Steel

Important - Dimensions may vary, if critical please contact sales for confirmation