



JV090004
Stainless Steel
2-Piece Ball Valve
c/w Operating Lever
BSPB Threaded



A versatile and robust two-piece stainless steel ball valve suitable for a wide range of isolation applications.

The quarter turn operation in conjunction with the PTFE seats provides fast positive isolation.

This valve can be locked in either the open or closed position.

Approvals, Features & Benefits

- PTFE seats
- Full bore
- Lever operated
- Lockable in the open & closed position
- Blow-out proof stem

Pressure & Temperature

Pressure range :-
PN63 rated

Temperature range*:-
-20°C to 200°C

* Dependent on pressure

BSPB	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
A	52	52	55	62	74	80	92	106	145	168	200
B	96	96	96	110	133	133	172	172	220	245	310
C	51	51	52	59	72	78	88	96	125	138	165
D	12	12	15	20	25	32	38	49	65	78	100
Weight Kg	0.2	0.2	0.2	0.3	0.5	0.8	1.1	1.5	3.6	5.5	9.3

MATERIALS	
Body	Stainless Steel (316)
Ball	Stainless Steel (316)
Stem	Stainless Steel (316)
Seats	PTFE / RTFE
Lever	Stainless Steel (201)

Important - Dimensions may vary, if critical please contact sales for confirmation