



JV090018
Stainless Steel
2-Piece Ball Valve
c/w Operating Lever
Flanged
PN16



A versatile and robust two-piece stainless steel ball valve suitable for a wide range of isolation applications.

The quarter turn operation in conjunction with the PTFE seats provides fast positive isolation.

This valve can be locked in either the open or closed position.

Approvals, Features & Benefits

- Face to face: DIN 3202 part 1 - F4/F5
- Blow-out proof stem
- Lockable device when lever is fitted
- Full bore

Pressure & Temperature

Pressure range :-
PN16 rated

Temperature range*:-
-20°C to 200°C

* Dependent on pressure

DN	15	20	25	32	40	50	65	80	100	125	150	200	250
L	115	120	125	130	140	150	170	180	190	325	350	400	450
W	169	169	206	206	267	267	298	390	390	743	743	925	1050
H	86	89	104	109	130	135	145	166	181	240	257	324	378
d	15	20	25	32	38	50	63	76	100	125	150	200	250
Weight Kg	2.2	2.6	3.65	6.12	6.85	9.65	15.2	19.6	27.3		53	80	

MATERIALS	
Body	Stainless Steel (CFM8)
Ball (DN15-100)	Stainless Steel (CFM8)
Ball (DN125-250)	Stainless Steel (316)
Seats	PTFE
Stem	Stainless Steel (316)