



JV090021
Stainless Steel
3-Way T-Ported
Ball Valve
ISO 5211 Mount
c/w Operating Lever
Flanged
PN16



A three-way, T-Ported stainless steel ball valve making them suitable for many applications where fluid diversion is required.

This valve may be locked in various positions when fitted with a lever.

Approvals, Features & Benefits

- 3-Way • T-Ported
- ISO 5211 top mounting pad
- Lockable device when lever is fitted
- Full bore
- Blowout proof stem

Pressure & Temperature

Pressure range :-
PN16 rated

Temperature range*:-
-20°C to 200°C

* Dependent on pressure

DN	15	20	25	32	40	50	65	80	100	150
A	160	165	180	234	234	273	300	305	369	480
B	15	20	25	32	40	50	65	76	96	148
ISO 5211	F03/F04	F03/F04	F04/F05	F07	F07	F07	F10	F10	F10	F14
Torque (Nm)*	29	35	40	49	49	104	114	235	293	553
Weight Kg	4.6	6.2	9.5	13	13	17	27	32	49	105

* Torque calculated at zero pressure includes 25% safety, add 25% for dry duty.

MATERIALS

Body	Stainless Steel (CFM8)
Ball	Stainless Steel (CF8M)
O-ring	Viton
Seats	PTFE
Stem	Stainless Steel (CF8M)

Ball Position



Important - Dimensions may vary, if critical please contact sales for confirmation