



JV240028
Ductile Iron Body
NBR Lined
Marine Quality
Butterfly Valve
c/w Pneumatic Actuator
Length to EN558-1 series 13
Double Flange Type
PN6/10/16, ANSI 150 & JIS 5/10K
(Specify when enquiring)



The JV240028 is a quality valve with a stream lined disc for high Kv/Cv values, low pressure loss and energy costs. Especially suitable for applications where weight and space-saving are important.

This valve is supplied completely assembled with either single (spring return) or double acting pneumatic actuators.

All valve and actuator packages are tested and issued with certification confirming the actuators functionality before despatch.

Approvals, Features & Benefits**

- Lloyds, DNV, ABS & BV type approval
- Face to face acc. EN558-1 series 13
- 3.1 & 3.2 certification on request
- Complete assembled package
- Air connection to Namur/VDE 3845 on actuator
- Double or single (spring return) acting actuator

**Valve only & dependent on construction materials

Pressure & Temperature

Pressure range:-

50-200mm: 16 Bar
250-1200mm: 10 Bar

Temperature range*:-

NBR Liner: 0°C to 80°C
EPDM Liner: -30°C to 110°C
Viton Liner: 0°C to 200°C

DN (other sizes available)	40	50	65	80	100	125	150	200	250	300
A	40	52	68	82	104	127	151	201	252	304
B	61	67	74	82	99.5	111.5	134	172	203	223
C	113	118	126	133	147	160	180	204	245	270
D	106	108	112	114	127	140	1470	152	165	178
E* (s)	109	109	109	120	133	143	191	(m)	230	262
E* (d)	109	109	109	109	109	120	133	156	191	208
F (s)	189	189	189	210	229	264	337	377	412	488
F (d)	189	189	189	189	189	210	229	266	337	377
K	-	-	-	-	-	-	5.4	25	43	63
L	-	-	-	-	-	-	56	132	190	246
Weight Kgs (s)	9	10	11.4	13.5	19.9	24.8	36.3	69.5	100	134
Weight Kgs (d)	8.8	9.8	10.6	11.8	15.4	21	27.7	51.9	68.7	93.7

(s) Single acting (d) Double acting (m) Mounting kit required - please contact sales for height dimension

ACTUATOR SPECIFICATIONS	
Enclosure	IP68 Watertight (IP68 5m 120hr)
Power Supply	110V & 250V AC 50/60Hz / 24V AC 50/60Hz / 24VDC / 380V & 440V 3PH
Indicator	Dome Type Mechanical
Limit Switches	2 x Open / 2 x Close, SPDT, 250V AC
Space Heater	110/220V AC Anti-condensation
Travel Angle	90° ± 5°
Casing Material	Aluminium Alloy, Dry Power Polyester Coated
Terminal Block	Push Button
Ambient Temperature	-20 to 60°C
Mechanism	Scotch-Yoke (JV-E05 - Spur Gear Type)

ACTUATOR OPTIONS	
LC	Local Control (with torque switches) - Available for models JV-E16 to JV-E120
SM	Super Modulating Unit Input / Output 4-20mA, 0-1V, 2-10V, 0-5V & 1-5V all in one unit (Available for 24VDC, 110VAC & 220VAC)
MC	Modulating Control Unit Input / Output 4-20mA (Only available for 110 & 220VAC)

BUTTERFLY VALVE MATERIALS	
Body	Ductile Iron (GGG40)
Liner	NBR - Option of EPDM & Viton on request
Disc	Aluminium Bronze (AB2) - Option of Stainless Steel (1.4408) on request
Shaft	Stainless Steel

*Special actuator mounting kit required for temperatures above 70°C, contact sales for details and overall height dimensions