



JV240031

Nickel Plated Brass Electric Operated WRAS Approved Ball Valve c/w JV-E Electric Actuator BSPP Threaded





The JV240031 is a WRAS approved, brass bodied full bore, ball valve suitable for a many applications including potable water offering reliability at an economical cost.

This valve is supplied completely assembled with a JV-E electric actuator which is small, lightweight and compact in design but still offering high output torques.

All valve and actuator packages are tested and issued with certification confirming the actuators functionality before despatch.

Approvals, Features & Benefits

- WRAS approved for potable water
- Full bore minimizes pressure drop
- Complete assembled package
- Various voltage options
- Manual override on actuator
- Lightweight & compact
- Visual position indicator on actuator

Pressure & Temperature

Pressure range:-

PN40 rated

Temperature range*:--20°C to 95°C

BSPP	1/2	3/4	1	11⁄4	11/2	2
Α	59	69	83	94	102	124
В	15	20	25	32	40	50
C*	154	157	161	166	182	189
D	124	124	124	124	124	124
Operation Time 90° 50/60hz Sec.	13	13	13	13	13	13
Actuator Type	JV-E05	JV-E05	JV-E05	JV-E05	JV-E05	JV-E05
Weight Kg	1.58	1.71	2	2.25	2.46	3.55

ACTUATOR SPECIFICATIONS					
Enclosure	IP68 Watertight (IP68 5m 120hr)	Travel Angle	90° ± 5°		
Power Supply	110V & 250V AC 50/60Hz / 24V AC 50/60Hz / 24VDC / 380V & 440V 3PH	Casing Material	Aluminium Alloy, Dry Power Polyester Coated		
Indicator	Dome Type Mechanical	Terminal Block	Push Button		
Limit Switches	2 x Open / 2 x Close, SPDT, 250V AC	Ambient Temperature	-20 to 60°C		
Space Heater	110/220V AC Anti-condensation	Mechanism	Spur Gear Type		

ACTUATOR OPTIONS		
SM	Super Modulating Unit Input / Output 4-20mA, 0-1V, 2-10V, 0-5V & 1-5V all in one unit (Available for 24VDC, 110VAC & 220VAC)	
MC	Modulating Control Unit Input / Output 4-20mA (Only available for 110 & 220VAC)	

BALL VALVE MATERIALS	
Body	Brass - Nickel Plated
Ball	Brass - Chrome Plated
Seats	PTFE
Stem	Brass - Nickel Plated

^{*}Special actuator mounting kit required for temperatures above 70°C, contact sales for details and overall height dimensions