



JV060006
Cast Iron
PN16 Rated
DIN3202-F4 Gate Valve
Flanged PN16



A economic cast iron, full bore gate valve with a brass seat and stainless steel stem ideally suited for water applications.

Features, Benefits & Approvals

- Conforms to DIN3202-F4
- Inside screw with non-rising stem
- Cast brass seat
- Stainless steel stem
- Bolted bonnet

Pressure & Temperature

Maximum pressure:-
PN16 rated

Temperature range:-
-10°C to 120°C

SIZE	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
A	140	150	170	180	190	200	210	230	250	270
B	230	210	230	265	303	375	430	524	650	740
Flange PCD	110	125	145	160	180	210	240	295	355	410
Flange Bolts	4 x M16	4 x M16	4 x M16	8 x M16	8 x M16	8 x M16	8 x M20	12 x M20	12 x M24	12 x M24
Weight Kg	10	12	15	19	27	35	50	60	97	132

MATERIALS

Body & Bonnet	Cast Iron (GG25)
Wedge	Cast Iron (GG25)
Body & Wedge Trim	Brass
Stem	Stainless Steel (A304)
Stem Nut	Brass
O-Ring	EPDM
Packing	Graphite
Handwheel	Cast Iron (GG25)