



## JV060015

**Cast Iron  
Marine Duty  
PN16 Rated  
Gate Valve**

**Flanged PN16/10**

Other flange drillings or undrilled on request



Good quality inside screw, non rising stem, non rising handwheel. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

### Approvals, Features & Benefits

- Specifications to DIN 3352 T2
- Marine style with open & shut indicator
- Bolted bonnet
- Inside screw non-rising stem.

### Pressure & Temperature

Maximum pressure:-  
DN25-DN150 : PN10 rated  
DN175-DN300 : PN6 rated

Temperature range:-  
-10°C to 120°C

SIZE*	DN25	DN32	DN40	DN50	DN65	DN80	DN100
<b>L</b>	125	130	140	150	170	180	190
<b>H</b>	170	185	240	255	295	315	345
<b>Flange PCD</b>	85	100	110	125	145	160	180
<b>Flange Bolts</b>	4 x M12	4 x M16	4 x M16	4 x M16	4 x M16	8 x M16	8 x M16
<b>Weight Kg</b>	5.5	7.8	10.5	12	17	21	28

SIZE*	DN125	DN150	DN175	DN200	DN250	DN300
<b>L</b>	200	210	210	230	250	270
<b>H</b>	400	430	515	530	635	725
<b>Flange PCD</b>	210	240	270	295	350	400
<b>Flange Bolts</b>	8 x M16	8 x M20	8 x M20	8 x M20	12 x M20	12 x M20
<b>Weight Kg</b>	36	46	54	62	96	140

\* Other flange drillings and sizes available on request

STANDARD MATERIALS	OPTIONAL MATERIALS (Others available on request)	
<b>Body</b>	Cast Iron (GG25)	
<b>Disc</b>	Bronze (LG2)	
<b>Stem</b>	Special Brass (SoMs 59)	Stainless Steel
<b>Bonnet</b>	Cast Iron (GG25)	