



**133**  
**Bronze**  
**PN16**  
**Marine**  
**Globe Valve**  
**Flanged PN16**

Other flange drillings or undrilled on request



Suitable for cold and hot water, seawater, wet and saturated steam, oil and other neutral non aggressive liquids.

The valve provides a leak tight shut off with the capability of being used partially open to regulate flow.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

**Features, Benefits & Approvals**

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Bolted cover, screw lift, rising stem
- Outside screw & yoke
- Marine style with open & shut indicator
- Screw lift or SDNR pattern

**Pressure & Temperature**

PN16 rated

Contact us for full details on working pressure and temperatures

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
<b>A</b>	108	117	127	146	159	191	216	254	305	330	356
<b>B</b>	95	105	115	140	150	165	185	200	220	280	
<b>C (Open)</b>	166	166	194	200	207	236	243	264	324	340	
<b>D</b>	125	125	125	125	160	160	200	200	250		
<b>Weight Kg</b>	5	5	7	8	9	13	17	22	36	61	

STANDARD MATERIALS		OPTIONAL MATERIALS	
<b>Body</b>	LG2 Bronze	LG2 Bronze, AB2 Ali-Bronze, AB4 Ali-Bronze	
<b>Disc</b>	LG2 Bronze	Stainless Steel	
<b>Spindle</b>	Manganese Bronze		
<b>Bonnet</b>	LG2 Bronze	LG2 Bronze, AB2 Ali-Bronze, AB4 Ali-Bronze	

Do you require class approved valves? Contact sales for availability.

