



**133L**  
**Bronze**  
**PN16**  
**Angled**  
**Marine**  
**Globe Valve**  
**Flanged PN16**

Other flange drillings or undrilled on request



Suitable for cold and hot water, seawater, wet and saturated steam, oil and other neutral non aggressive liquids.

The valve provides a leak tight shut off with the capability of being used partially open to regulate flow.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

**Features, Benefits & Approvals**

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Bolted cover, screw lift, rising stem
- Outside screw & yoke
- Marine style with open & shut indicator
- Screw lift or SDNR pattern

**Pressure & Temperature**

PN16 rated

Contact us for full details on working pressure and temperatures

| SIZE             | DN15 | DN20 | DN25 | DN32 | DN40 | DN50 | DN65 | DN80 | DN100 |
|------------------|------|------|------|------|------|------|------|------|-------|
| <b>A</b>         | 70   | 75   | 85   | 95   | 100  | 115  | 125  | 135  | 146   |
| <b>B</b>         | 95   | 105  | 115  | 140  | 150  | 165  | 185  | 200  | 220   |
| <b>C (Open)</b>  | 158  | 158  | 177  | 185  | 188  | 210  | 218  | 236  | 298   |
| <b>D</b>         | 125  | 125  | 125  | 125  | 160  | 160  | 200  | 200  | 250   |
| <b>Weight Kg</b> | 4    | 4    | 6    | 8    | 8    | 12   | 16   | 21   | 31    |

| STANDARD MATERIALS | OPTIONAL MATERIALS                         |
|--------------------|--|
| <b>Body</b>        | LG2 Bronze, AB2 Ali-Bronze, AB4 Ali-Bronze |
| <b>Disc</b>        | Stainless Steel                            |
| <b>Spindle</b>     | Manganese Bronze                           |
| <b>Bonnet</b>      | LG2 Bronze, AB2 Ali-Bronze, AB4 Ali-Bronze |

Do you require class approved valves? Contact sales for availability.

