



JV070018

Cast Iron Body Stainless Steel Disc Globe Valve Flanged PN16

Other flange drillings or undrilled on request



This bolted bonnet globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to FTF series 1 according to DIN EN 5581 (DIN 3202-1 series F1).

Features, Benefits & Approvals

- DIN 3202-1 Series F1
- Screw lift
- Bolted bonnet
- Gland sealed
- Stainless steel disc
- Rising stem

Pressure & Temperature

Pressure range:-
PN16 rated

Temperature range*:-
-10°C to 120°C

* Not suitable for steam, contact sales for alternative

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200
A	130	150	160	180	200	230	290	310	350	400	480	600
B (Open)	183	191	216	255	277	304	335	380	426	480	555	660
C	100	100	120	120	160	160	180	200	250	250	320	360
Weight Kg	3.3	4	5.5	8.5	10.75	14.57	19.3	26.7	35.4	59	78	136

MATERIALS

Body	Cast Iron
Bonnet	Cast Iron
Stem	Stainless Steel
Disc	Stainless Steel