



JV070041

Bronze Union Bonnet Marine Globe Valve Flanged PN16

Other flange drillings or undrilled on request



Bronze secured union bonnet, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- Metal seated
- Rising stem
- Secured union bonnet

Pressure & Temperature

16 Bar @ 120°C
10 Bar @ 180°C

SIZE	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
A	90	95	105	115	140	150	165	185	200	220
H (Open)	95	95	110	115	135	145	165	230	250	260
L	70	70	80	90	105	120	140	180	200	230
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16
Weight Kg	1.4	1.8	2.1	2.6	4.2	5.2	7.5	11	14.5	21

STANDARD MATERIALS		OPTIONAL MATERIALS	
Body	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	
Bonnet	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	
Stem	Brass (SoMs59)	Bronze (CuSn6)	
Disc	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	

Do you require class approved valves? Contact sales for availability.

