



## JV070042

**Bronze  
Union Bonnet  
Screw Down Non Return  
Marine Globe Valve  
Flanged PN16**

Other flange drillings or undrilled on request



Bronze secured union bonnet, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

The valve provides a leak tight shut off with a non-return design, preventing reverse flow when in the open position.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

### Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw Down Non Return (SDNR)
- Metal seated
- Rising stem
- Secured union bonnet

### Pressure & Temperature

- 16 Bar @ 120°C
- 10 Bar @ 180°C

SIZE	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
<b>A</b>	90	95	105	115	140	150	165	185	200	220
<b>H (Open)</b>	95	95	110	115	135	145	165	230	250	260
<b>L</b>	70	70	80	90	105	120	140	180	200	230
<b>Flange</b>	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16
<b>Weight Kg</b>	1.4	1.8	2.1	2.6	4.2	5.2	7.5	11	14.5	21

STANDARD MATERIALS		OPTIONAL MATERIALS	
<b>Body</b>	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	
<b>Bonnet</b>	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	
<b>Stem</b>	Brass (SoMs59)	Bronze (CuSn6)	
<b>Disc</b>	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	

Do you require class approved valves? Contact sales for availability.

