



**JV070061**  
**Cast Steel Body**  
**Stainless Steel Disc**  
**Angled**  
**Globe Valve**  
**Flanged PN40**  
PN16 Flanged on request



This bolted bonnet globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to CTF series 8 according to DIN EN 5581 (DIN 3202-1 series F32).

**Features, Benefits & Approvals**

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- DIN 3202-1 Series F32
- Screw lift
- Bolted bonnet
- Gland sealed
- Stainless steel disc
- Rising stem

**Pressure & Temperature**

Pressure range:-  
PN40 rated\*\*

Temperature range:-  
-10°C to 300°C\*\*\*

\*\* PN16 rated for PN16 flange option  
\*\*\* Higher temperature on request

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125
<b>A</b>	90	95	100	105	115	125	145	155	175	200
<b>B</b>	155	155	160	170	210	210	225	260	305	310
<b>Flange</b>	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40
<b>Weight Kg</b>	3.8	4	5	7	10	12	17	23	33	50

SIZE	DN150	DN175	DN200	DN250	DN300	DN350	DN400	DN450	DN500	DN600
<b>A</b>	225	250	275	325	375	425	475	500	525	550
<b>B</b>	350	420	420	485	530	610	660	700	765	810
<b>Flange</b>	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40
<b>Weight Kg</b>	70	90	110	155	215	275	360	395	485	650

**MATERIALS**

<b>Body</b>	Cast Steel
<b>Bonnet</b>	Cast Steel
<b>Stem</b>	Stainless Steel
<b>Disc</b>	Stainless Steel