



JV070063

**Cast Steel Body
Bronze Disc
Globe Valve**

Flanged PN16/10

Other flange drillings or undrilled on request



This bolted bonnet globe valve with a bronze valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to FTF series 1 according to DIN EN 5581 (DIN 3202-1 series F1).

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- DIN 3202-1 Series F1
- Screw lift
- Bolted bonnet
- Gland sealed
- Bronze disc
- Rising stem

Pressure & Temperature

15-200mm
16 Bar @ 120°C
10 Bar @ 180°C

250-300mm
10 Bar @ 120°C
6 Bar @ 180°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
A	130	150	160	180	200	230	290	310	350	400	480	600	730	850
B (Open)	194	198	202	286	314	325	370	424	479	552	636	760	885	1035
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN10	PN10
Weight Kg	4.6	5.3	6	11	12.3	16	28	36	50	63	86	175	326	375

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem	Phosphor Bronze
Disc	Bronze