



**F7352**  
Bronze Body  
Bronze/Brass Disc  
Screw Down Non Return  
Angled  
JIS Marine  
Globe Valve  
Flanged JIS-5K



Bronze metal seated gland packed globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

This valve has a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

**Features, Benefits & Approvals**

- JIS 5K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw Down Non Return (SDNR)
- 15-40mm Secured screwed bonnet
- 50-65mm Bolted bonnet
- Gland sealed
- Bronze / brass disc
- Rising stem

**Pressure & Temperature**

**Non-shock water:**

7 Bar @ 120°C

**Air, Gas, Steam, Pulsating Water:**

5 Bar @ 205°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65
L1	55	60	65	80	85	100	115
H1	120	130	145	150	165	200	220
A	80	85	95	115	120	130	155
PCD	60	65	75	90	95	105	130
Holes	4 x 12	4 x 12	4 x 12	4 x 15	4 x 15	4 x 15	4 x 15
Weight Kg	1.98	2.73	3.44	4.77	5.99	10.10	15.60

MATERIALS	
Body	Bronze
Bonnet	Bronze / Brass
Stem	Brass
Disc	Bronze / Brass

Do you require class approved valves? Contact sales for availability.

