



F7410

Bronze Body Bronze/Brass Disc Screw Down Non Return Angled JIS Marine Globe Valve Flanged JIS-16K



Bronze metal seated gland packed globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

This valve has a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- JIS 16K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- 15-40mm Secured screwed bonnet
- 50-65mm Bolted bonnet
- Gland sealed
- Bronze / brass disc
- Rising stem

Pressure & Temperature

Non-shock water:

22 Bar @ 120°C

Air, Gas, Steam, Pulsating Water:

16 Bar @ 205°C

SIZE	DN15	DN20	DN25	DN32	DN40
L1	70	75	85	95	100
H1	120	130	145	150	165
Α	95	100	125	135	140
PCD	70	75	90	100	105
Holes	4 x 15	4 x 15	4 x 19	4 x 15	4 x 19
Weight Kg	2.73	3.65	5.16	6.72	8.13

MATERIALS		
Body	Bronze	
Bonnet	Bronze / Brass	
Stem	Brass	
Disc	Bronze / Brass	

Do you require class approved valves? Contact sales for availability.











