



JV071015
Cast Steel Body
Stainless Steel Disc
Globe Valve
Flanged PN40



This bolted bonnet globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to FTF series 1 according to DIN EN 5581 (DIN 3202-1 series F1).

Features, Benefits & Approvals

- 3.1 available on request
- DIN 3202-1 Series F1
- Screw lift
- Bolted bonnet
- Gland sealed
- Stainless steel disc
- Rising stem

Pressure & Temperature

Pressure range:-
PN40 rated

Temperature range:-
-20°C to 400°C

DN	15	20	25	32	40	50	65	80	100	125	150	200
A	130	150	160	180	200	230	290	310	350	400	480	600
B	155	160	180	180	220	230	280	285	315	523	541	699
Flange	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40
Weight Kg	3.5	4.3	6.3	7.3	12.5	15	22.5	27.5	42	67	99	200

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem	Stainless Steel
Disc & Seat	Stainless Steel