


## JV080024

**Stainless Steel Body & Disc  
Viton Seated  
Spring-Loaded  
Check (Non-Return) Valve  
Multi-Flange Wafer Type**

15mm - 80mm  
PN6/10/16/25/40, ANSI150 & ANSI300  
100mm  
PN10/16/25/40, ANSI150 & ANSI300



An economical spring-loaded non-return valve with a stainless steel body and disc.

It can be fitted in the horizontal position or in the vertical position with the flow going upwards.

### Approvals, Features & Benefits

- Lightweight & economic
- Spring loaded
- Suitable for upward & horizontal flow
- Space saving

### Pressure & Temperature

Pressure range:-  
PN52 Rated

Temperature Range:-  
0°C to 200°C

SIZE	15	20	25	32	40	50	65	80	100
<b>A</b>	43	48	58	68	75	94	113	129	159
<b>B</b>	17	20	22	28	32	40	46	50	60
<b>Weight Kg</b>	0.11	0.18	0.26	0.40	0.55	1.00	1.50	2.00	3.20

### MATERIALS

<b>Body</b>	Stainless Steel (AISI 316)
<b>Disc</b>	Stainless Steel (AISI 316L)
<b>Seat</b>	Viton
<b>Spring</b>	Stainless Steel (AISI 316)