



JV080033

**Bronze
NBR Seals
Swing Type
Marine Quality
Check (Non-Return) Valve**

**Flanged
PN16/10**

Other flange drillings or undrilled on request



A marine duty bronze, swing type (flapper) check valve with a bronze flap and NBR seals suitable for cold and hot water, seawater, fuel oil and other non-aggressive medium.

It can be fitted in the horizontal position or in the vertical position with the flow going upwards.

Features, Benefits & Approvals

- Length to DIN 3202 F6
- 3.1 material certificates on request
- Marine quality materials
- Bolted bonnet

Pressure & Temperature

Maximum pressure:-

DN32-125 : PN16 rated
DN150-200 : PN10 rated
DN250-300 : PN6 rated

Temperature range:-

0°C to 100°C

DN	32	40	50	65	80	100	125	150
L	180	180	200	240	260	300	350	400
H	95	95	100	115	135	145	160	180
D	140	150	165	185	200	220	250	285
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16
Weight Kg	8	8	10	15	21	26	42	55

DN	200	200	250	250	300	300
L	500	500	600	600	700	700
H	270	270	320	320	350	350
D	340	340	405	395	460	445
Flange	PN16	PN10	PN16	PN10	PN16	PN10
Weight Kg	112	112	165	165	250	250

MATERIALS	
Body	Bronze (LG2)
Bonnet	Bronze (LG2)
Seat	NBR (Option of EPDM)
Shaft	Copper Alloy (CZ 121)
Flap	Bronze (LG2)