



JV150005
Stainless Steel
Y Type Strainer
Flanged PN16



The JV150005 stainless steel 'Y' type strainer with a stainless steel screen ideally suited for use in the water distribution, gas oil, steam and petrochemical applications to protect meters, pumps, valves and other pipeline equipment.

Approvals, Features & Benefits

- Suitable for a wide range of duties
- Y type for efficient straining
- Easy to remove screen for cleaning
- Drain plug

Pressure & Temperature

Maximum pressure:-
16 bar
Temperature range:-
-20°C to 450°C

See pressure/temperature chart below

SIZE	DN25	DN40	DN50	DN65	DN80	DN100	DN150	DN200	DN250	DN300
L	160	200	230	290	310	350	480	600	730	805
D	115	150	165	185	200	220	285	340	405	460
C	85	110	125	145	160	180	240	295	355	410
B	25	40	50	65	80	100	150	200	250	300
T	16	16	18	18	20	20	22	24	26	28
R	68	88	102	122	138	158	212	268	320	370
F	1	2	2	2	2	2	2	2	2	3
Drain Plug (BSPT)		½"	½"	½"	½"	½"	½"			
Flange Bolt Holes	4 x 14	4 x 18	4 x 18	4 x 18	8 x 18	8 x 18	8 x 22	12 x 22	12 x 26	12 x 26
Mesh Perforation	1.5	2	2	2	2	2	2			
Weight Kg	3.4	6.2	9	16.8	18.4	23	48	98	145	216

MATERIALS

Body & Bonnet	Stainless Steel (A351-CF8M)
Screen & Drain Plug	Stainless Steel (316)
Gland Bolt	Stainless Steel (304)
Gasket	PTFE

Pressure/Temperature

