



## WADE SAFETY RELIEF VALVES


### 6000 SERIES

### SAFETY RELIEF VALVE FOR AIR & INERT GASES



Part No. 6000 Compact  
Part No. 6100 Standard  
Part No. 6200 Side Outlet Discharge

Fig 6000/6100



SIZE	R	A	B	C	D	E
DN06	¼	45	-	-	-	-
DN06	¼	-	15	88	33	136
DN10	⅜	-	15	88	33	136
DN15	½	-	15	88	33	136
DN20	¾	-	18	90	33	141
DN25	1	-	21	97	33	151




Fig 6200

SIZE	R	A	B	C	D	E	F
DN15	½	15	88	33	136	40.0	30.5
DN20	¾	18	90	33	141	48.5	36.0
DN25	1	21	97	33	151	58.5	40.0

Models 6000/6100 are high lift safety relief valves with atmospheric discharge and the Model 6200 has a side outlet discharge. All are suitable for air and inert gas applications and are of brass construction with a stainless steel spring. The flow rates are measured in accordance with BS6759 Part 2: 1984. These valves re-seat 10% below the set pressure.

#### Features & Benefits

- Approved to BS6759.
- Resilient faced valve lid for leak tight seal.
- Economical & reliable.

#### Pressure & Temperature

Pressure range:-

1.8 to 12.5 bar.\*

Temperature Range:-

-15°C to 140°C.

\* 20.7 bar available on request

**THIS PRODUCT IS STOCKED UNSET & CAN BE  
SET TO YOUR EXACT REQUIREMENTS**