



## ABS & uPVC VALVES

### BVL-T RANGE

#### uPVC 3 WAY 'L' & 'T' PORTED BALL VALVE



- Part No. BVL-11P ('L' PORTED WITH BSP THREADED ENDS)**  
**Part No. BVT-11P ('T' PORTED WITH BSP THREADED ENDS)**  
**Part No. BVL-13P ('L' PORTED WITH SOLVENT WELD ENDS)**  
**Part No. BVT-13P ('T' PORTED WITH SOLVENT WELD ENDS)**  
**3 WAY BALL VALVE WITH uPVC BODY & EPDM SEALS**

These versatile 3 way ball valves are suitable for a wide range of applications offering an unobstructed full bore and are available with 'L' or 'T' ported configurations.

uPVC is lightweight and has excellent resistance to chemicals and abrasion, is tasteless and odourless making it ideal for use with potable water systems and most food products. uPVC is resistant to most solutions of acids, alkalis, salts and solvents which can be mixed with water.

#### Features & Benefits

- WRAS Approved.
- uPVC Approved to BS4346 part 1.
- Lightweight.
- Full bore.
- Lever operated.
- Materials suitable for a wide range of applications.

#### Pressure & Temperature

Pressure range:-  
Up to 10 bar

Temperature Range:-  
0°C to 60°C.

SIZE	3/8	1/2	3/4	1	1 1/4	1 1/2	2
A	57	57	62	74	82	104	117
B	80	80	87	104	115	145	160
C	112	112	123	147	169	209	230
D	9.5 (3/8")	12.7 (1/2")	19.1 (3/4")	25.4 (1")	31.8 (1 1/4")	38.1 (1 1/4")	50.8 (2")
E	85	85	85	100	100	127	127

\* BVL-T-11 BSPP thread size in brackets

**THESE VALVES CAN BE SUPPLIED WITH ELECTRIC  
& PNEUMATIC OPERATED ACTUATORS**