



STORZ
JV120100
Male Threaded Adaptors
JV120101
Female Threaded Adaptors



The Storz coupling system connects using interlocking hooks and flanges. It is widely used in firefighting applications in Portugal, Denmark, Germany, Austria, Switzerland, Sweden, Netherlands, Israel, Greece, Australia and the United States.

DN	A	G*	DIN	JV120100 - Male Thread					JV120101 - Female Thread			
				Aluminium	Brass	Bronze	Ali-Bronze	St. Steel	Aluminium	Brass	Bronze	St. Steel
D-25	31	R ½	-	✓	✓						✓	✓
D-25	31	R ¾	-	✓	✓					✓	✓	✓
D-25	31	R 1	14306	✓	✓	✓	✓	✓		✓	✓	✓
32	44	R 1¼	-	✓	✓						✓	
38	51	R 1¼	-	✓	✓							
38	51	R 1½	-	✓	✓	✓		✓		✓	✓	
38	51	R 2	-	✓	✓	✓						
C-52	66	R 1	-	✓	✓	✓		✓		✓	✓	✓
C-52	66	R 1¼	-	✓	✓	✓			✓	✓	✓	
C-52	66	R 1½	-	✓	✓	✓			✓	✓	✓	
C-52	66	R 2	14307	✓								
C-52	66	R 2	86204		✓	✓		✓	✓	✓	✓	✓
C-52	66	R 2½	-	✓	✓	✓				✓	✓	✓
65	81	R 1½	-		✓	✓						
65	81	R 2	-	✓	✓	✓				✓	✓	✓
65	81	R 2½	-	✓	✓	✓				✓	✓	✓
65	81	R 3	-	✓	✓	✓						
B-75	89	R 2	-	✓	✓	✓		✓		✓	✓	
B-75	89	R 2½	14308	✓								
B-75	89	R 2½	86205		✓	✓		✓		✓	✓	✓
B-75	89	R 3	-	✓	✓	✓				✓	✓	✓
100	115	R 4	-	✓		✓		✓		✓	✓	
A-110	133	R 4	14309	✓	✓	✓		✓		✓	✓	
A-110	133	R 4½	14309	✓	✓	✓		✓				
A-110	133	R 5	-	✓								
125	148	R 4	-	✓		✓				✓	✓	
125	148	R 4½	-								✓	
125	148	R 5	-	✓		✓		✓		✓	✓	
125	148	R 6	-								✓	
F-150	160	R 6	-	✓		✓		✓		✓	✓	
38	51	NH 1½	-		✓							
C-52	66	NH 1½	-	✓		✓				✓	✓	✓
C-52	66	NH 2½	-	✓	✓	✓				✓	✓	✓
65	81	NH 2½	-	✓	✓	✓				✓	✓	✓
B-75	89	NH 2½	-	✓		✓				✓	✓	
100	115	NH 4	-	✓		✓						
100	115	NH 4½	-	✓		✓						
A-110	133	NH 4	-	✓								
A-110	133	NH 4½	-	✓		✓						
125	148	NH 4	-			✓						
125	148	NH 4½	-			✓						
B-75	89	NPT 2½	-			✓						
A-110	133	NPT 4	-			✓						✓
125	148	NPT 5	-			✓						
125	148	NPT 6	-			✓						

✓ = Available * R = BSP NH = NST National Standard Thread for fire hose connections nach NFPA 1963 (USA) NPT = ANSI B 2.4-1966 (USA)



STORZ
JV120102
Delivery Hose Coupling
JV120103
Suction Hose Coupling
JV120104
Blank Cap c/w Chain



The Storz coupling system connects using interlocking hooks and flanges. It is widely used in firefighting applications in Portugal, Denmark, Germany, Austria, Switzerland, Sweden, Netherlands, Israel, Greece, Australia and the United States.

DN	A	B	L	DIN	JV120102 - Delivery Hose					JV120103 - Suction Hose				
					Aluminium	Brass	Bronze	Ali-Bronze	St. Steel	Aluminium	Brass	Bronze	Ali-Bronze	St. Steel
D-25-DS	31	15	50	-		✓	✓	✓	✓					
D-25-DS	31	19	50	-	✓	✓								
D-25-DS	31	25	50	14301	✓	✓	✓	✓						
32-DS	44	32	75	-		✓								
38-DS	51	38	75	-		✓	✓	✓						
C-52	66	52	55	14302	✓									
C-52	66	52	75	86202		✓	✓	✓	✓					
C-52-DS	66	25	90	-						✓	✓	✓	✓	
C-52-DS	66	32	90	-						✓	✓			
C-52-DS	66	38	90	-						✓	✓			
C-52-DS	66	45	90	-						✓	✓	✓	✓	
C-52-DS	66	52	90	14321						✓	✓	✓	✓	✓
65-DS	81	52	90	-						✓	✓	✓	✓	✓
65-DS	81	65	90	-						✓	✓	✓	✓	✓
B-75	89	38	80	-			✓	✓						
B-75	89	52	80	-		✓								
B-75	89	65	80	-		✓								
B-75	89	75	80	86203		✓	✓	✓	✓					
B-75	89	80	80	-		✓								
B-75-DS	89	52	125	-						✓				
B-75-DS	89	65	125	-						✓	✓			
B-75-DS	89	75	125	14322						✓	✓	✓	✓	
100-DS	115	100	150	-						✓		✓	✓	
A-110-DS	133	100	170	-						✓				
A-110-DS	133	110	170	14323						✓		✓	✓	
125-DS	148	125	200	-						✓		✓	✓	

DN	A	DIN	JV120104 - Blank Cap c/w Chain				
			Aluminium	Brass	Bronze	Ali-Bronze	St. Steel
D-25	31	14310	✓	✓	✓	✓	✓
38	51	-	✓	✓	✓	✓	
C-52	66	14311	✓				
C-52 L	66	86206L*		✓	✓	✓	✓
C-52 K	66	86206K*	✓	✓	✓	✓	
65	81	-	✓	✓	✓	✓	
B-75	89	14612	✓				
B-75 L	89	86207L*		✓	✓	✓	✓
B-75 K	89	86207K*		✓	✓	✓	✓
100	89	-	✓		✓	✓	
A-100	133	14313	✓	✓	✓	✓	
125	148	-	✓		✓	✓	
F-150	160	-	✓		✓	✓	

✓ = Available * K = Cap with control holes * L = Cap without control holes