



**233**  
**Bronze**  
**Marine Globe Valve**  
**Flanged PN16/10**

Other flange drillings or undrilled on request



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

**Features, Benefits & Approvals**

- DIN 86260
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- Metal seated
- Rising stem
- Bolted bonnet

**Pressure & Temperature**

- 15-125mm**  
16 Bar @ 120°C  
10 Bar @ 180°C
- 150-200mm**  
10 Bar @ 120°C  
6 Bar @ 180°C
- 250-300mm**  
6 Bar @ 120°C  
4 Bar @ 180°C
- 350-500mm**  
4 Bar @ 120°C  
2 Bar @ 180°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125
<b>A</b>	130	150	160	180	200	230	290	310	350	400
<b>B (Open)</b>	180	200	210	220	250	250	315	335	375	420
<b>Flange</b>	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16
<b>Weight Kg</b>	5	5.5	6	8	10	12	17	23	30	50

SIZE	DN150	DN175	DN200	DN250	DN300	DN350	DN400	DN450	DN500
<b>A</b>	480	550	600	730	850	980	1100	1200	1250
<b>B (Open)</b>	460	520	550	670	750	850	910	970	1095
<b>Flange</b>	PN10	PN10	PN10	PN10	PN10	PN10	PN10	PN10	PN10
<b>Weight Kg</b>	65	85	110	165	295	480	510	1150	1300

STANDARD MATERIALS		OPTIONAL MATERIALS	
<b>Body</b>	Bronze (LG2)	Ali-Bronze	
<b>Bonnet</b>	Bronze (LG2)		
<b>Stem</b>	Brass (SoMs59)	Bronze (CuSn6)	
<b>Disc</b>	Bronze (LG2)	Ali-Bronze	

Do you require class approved valves? Contact sales for availability.

