



233L

Bronze Angled Marine Globe Valve

Flanged PN16/10

Other flange drillings or undrilled on request



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- DIN 86260
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- Metal seated
- Rising stem
- Bolted bonnet

Pressure & Temperature

- 15-125mm**
16 Bar @ 120°C
10 Bar @ 180°C
- 150-200mm**
10 Bar @ 120°C
6 Bar @ 180°C
- 250-300mm**
6 Bar @ 120°C
4 Bar @ 180°C
- 350-500mm**
4 Bar @ 120°C
2 Bar @ 180°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125
A	90	95	100	105	115	125	145	155	175	200
B (Open)	160	170	170	190	210	220	260	280	300	340
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16
Weight Kg	3.8	4	5	7	9	11	16	20	25	40

SIZE	DN150	DN175	DN200	DN250	DN300	DN350	DN400	DN450	DN500
A	225	250	275	325	375	425	475	500	590
B (Open)	360	380	440	550	620	720	750	925	950
Flange	PN10	PN10	PN10	PN10	PN10	PN10	PN10	PN10	PN10
Weight Kg	50	75	95	155	225	360	400	650	800

STANDARD MATERIALS	OPTIONAL MATERIALS
Body	Bronze (LG2) / Ali-Bronze
Bonnet	Bronze (LG2)
Stem	Brass (SoMs59) / Bronze (CuSn6)
Disc	Bronze (LG2) / Ali-Bronze

Do you require class approved valves? Contact sales for availability.

