



333L

Bronze Short Length Angled Marine Globe Valve

Flanged PN16/10

Other flange drillings or undrilled on request



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- Metal seated
- Rising stem
- Bolted bonnet

Pressure & Temperature

15-125mm
16 Bar @ 120°C
10 Bar @ 180°C

150mm
10 Bar @ 120°C
6 Bar @ 180°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
A	65	70	75	90	95	105	115	125	140	175	200
B (Open)	135	140	155	160	180	190	210	230	280	315	340
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN10
Weight Kg	2.2	3	3.7	5	7	8.8	13	17	24	35	51

STANDARD MATERIALS		OPTIONAL MATERIALS
Body	Bronze (LG2)	Al-Bronze
Bonnet	Bronze (LG2)	
Stem	Brass (SoMs59)	Bronze (CuSn6)
Disc	Bronze (LG2)	Al-Bronze

Do you require class approved valves? Contact sales for availability.

