



433L

Bronze 1271-LK Type Angled Marine Globe Valve

Flanged PN16/10

Other flange drillings or undrilled on request



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- 1271-LK type
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- Metal seated
- Rising stem
- Bolted bonnet

Pressure & Temperature

15-150mm
16 Bar @ 120°C
13 Bar @ 180°C

200mm
10 Bar @ 120°C
8 Bar @ 180°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200
A	65	65	70	90	90	105	115	125	145	170	200	250
B (Open)	157	175	190	205	215	235	260	265	285	310	340	570
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN10
Weight Kg	4	5.5	6.2	8.4	10	12.8	23.2	31	41	65	89	127

STANDARD MATERIALS		OPTIONAL MATERIALS
Body	Bronze (LG2)	Ali-Bronze
Bonnet	Bronze (LG2)	
Stem	Brass (SoMs59)	Bronze (CuSn6)
Disc	Bronze (LG2)	Ali-Bronze

Do you require class approved valves? Contact sales for availability.

